

Planning (Industrial Zones) Technical Specifications 2024

Notifiable instrument NI2024–541

made under the

Planning Act 2023, s 51 (Technical specifications)

1 Name of instrument

This instrument is the *Planning (Industrial Zones) Technical Specifications 2024*.

2 Commencement

This instrument commences on 27 September 2024.

3 Technical specifications

I make the technical specifications at schedule 1.

4 Revocation

This instrument revokes the *Planning (Industrial Zones) Technical Specifications 2023* (NI2023-556).

George Cilliers
Chief Planner
13 September 2024



ZS3 – Industrial Zones Specifications

Table of Contents

Table of Contents	3
Industrial Zones planning technical specifications	6
Urban Structure and Natural Systems.....	7
Assessment Outcome 1	7
Assessment Outcome 2	7
Assessment Outcome 3	7
Site and Land Use	7
Assessment Outcome 4	7
Community use.....	7
Assessment Outcome 5	7
Assessment Outcome 6	8
Access and Movement	8
Assessment Outcome 7	8
Passive surveillance – public access	8
Fencing.....	8
Road network	8
Assessment Outcome 8	8
Public Space and Amenity	8
Assessment Outcome 9	8
Assessment Outcome 10	9
Signs.....	9
Built Form and Building Design	9
Assessment Outcome 11	9
Building height.....	9
Sustainability and Environment.....	9
Assessment Outcome 12	9
Site permeability.....	10
Water sensitive urban design	10
Assessment Outcome 13	10
Assessment Outcome 14	10

Site disturbance	10
Assessment Outcome 15	10
Assessment Outcome 16	10
Noise management – general.....	10
Emergency Management Plan – animal care facility	11
Bushfire prone area	11
Flood risk	11
Stormwater retention and detention.....	11
Stormwater management	11
Stormwater quality	12
Site contamination	12
Hazardous materials.....	12
Demolition	12
Parking, Services and Utilities.....	12
Assessment Outcome 17	12
Electric vehicle ready parking.....	12
Assessment Outcome 18	13
End of trip facilities – provision of facilities.....	13
End of trip facilities – design requirements of facilities	13
End of trip facilities – shower and change facilities	14
Table 1 – End of trip facilities – provision rates	15
Assessment Outcome 19	16
Number of car parking spaces	16
Accessible car parking spaces.....	16
Dimensions and access for car parking spaces.....	16
Safety	17
Pedestrian and cyclist access.....	17
Accessible path of travel.....	17
Table 2 and 3 – Parking rates and location requirements.....	17
Table 2 - Parking provision rates for IZ zones.....	17
Table 3 - Parking locational requirements.....	19
Assessment Outcome 20	19
Waste facilities	19
Assessment Outcome 21	19
Servicing and infrastructure	20

Battery storage	20
Demolition – utility endorsement	20
Loading docks and goods vehicles.....	20
External lighting.....	20
Encroachment of easements and rights-of-way	20

Industrial Zones planning technical specifications

The primary assessment consideration for a development application is the assessment outcomes in the Territory Plan. In demonstrating compliance with the assessment outcomes, consideration may be given to the relevant planning technical specifications which may serve as a benchmark. While all assessment outcomes are to be met, not all outcomes are covered by a specification.

Planning technical specifications are used as a possible solution or to provide guidance for identified aspects of a development proposal. The specifications may also be used as a reference or benchmark in the preparation and assessment of development proposals to demonstrate compliance with the assessment outcomes, and the Territory Plan.

Where a proposed development complies with a relevant provision in the planning technical specifications and the development comprehensively addresses the assessment outcome, further assessment regarding those specific provisions will not be required.

The Territory Planning Authority may consider advice or written support from a referral entity to demonstrate compliance with a relevant assessment outcome. Where endorsement from an entity is noted as a planning specification, entity referral may be required.

Consistent with the Industrial Zones Policy, this Industrial Zones Specification comprises specifications under seven categories:

- Urban Structure and Site;
- Access and Movement;
- Public Space and Amenity;
- Land Use and Development;
- Built Form and Building Form;
- Sustainability and Environment; and
- Parking, Services and Utilities.

These specifications will primarily be for development within industrial zones. However, these specifications may also be used in other circumstances where considered relevant.

Urban Structure and Natural Systems

The following specifications provide possible solutions that should be considered in the planning of a proposed development:

Assessment Outcome	1. Biodiversity connectivity is maintained across the landscape.
No applicable specification for this assessment outcome. Application must respond to the assessment outcome.	

Assessment Outcome	2. Loss of native habitat and biodiversity is avoided and/or minimised.
No applicable specification for this assessment outcome. Application must respond to the assessment outcome.	

Assessment Outcome	3. The health and functionality of waterways and catchments is maintained, including through application of water sensitive urban design principles.
No applicable specification for this assessment outcome. Application must respond to the assessment outcome.	

Site and Land Use

The following specifications provide possible solutions that should be considered in the planning of a proposed development:

Assessment Outcome	4. The functionality and usability of the development is appropriate for its intended purpose/use.
Specification	
Community use	4.1. An application for community uses demonstrate that the proposed use: a) Services the needs of the local workforce; or b) Requires a scale of building or level of amenity that is not compatible with other available land.

Assessment Outcome	5. The proposed use and scale of development are appropriate to the site and zone.
No applicable specification for this assessment outcome. Application must respond to the assessment outcome.	

Assessment Outcome 6. Adverse impacts of development on surrounding uses (both within a site and on adjoining sites) is minimised and industrial amenity protected.

No applicable specification for this assessment outcome. Application must respond to the assessment outcome.

Access and Movement

The following specifications provide possible solutions that should be considered in relation to access, travel modes and movement to and within a proposed development:

Assessment Outcome 7. The functionality and layout of the development is well connected to the surrounding area. This includes consideration of traffic flow, passive surveillance and active travel.

Specification

Passive surveillance – public access	7.1. Public access to shops and offices ancillary to industrial buildings are located to the front of buildings.
Fencing	7.2. Fencing visible from the public domain is at least 50% transparent.
Road network	7.3. Endorsement by Transport Canberra and City Services (TCCS) to confirm the road network can accommodate additional traffic likely to be generated by the development. Offsite works may be required to support additional traffic from a development.

Assessment Outcome 8. Access to, from and within the site permits safe and legible movement while catering for all users (including pedestrians). This includes consideration of vehicle manoeuvrability and access routes.

No applicable specification for this assessment outcome. Application must respond to the assessment outcome

Public Space and Amenity

The following specifications provide possible solutions that should be considered in relation to public areas (areas accessible to residents, visitors and community) and amenity outcomes associated with a proposed development:

Assessment Outcome 9. The development achieves reasonable solar access and microclimate conditions to public areas and streets to support their use by the community.

No applicable specification for this assessment outcome. Application must respond to the assessment outcome.

Assessment Outcome	10. Any advertising or signs are suitable for their context and do not have a detrimental impact on the surrounding area (for instance due to size or light emission).
Specification	
Signs	10.1. Signage located and sized according to the following table:

Location of Principal, Second and Third Party Signage				
	Ground Floor	1 st Storey	Above 1 st Storey	Free Standing Sign
Principal Signage	Y	Y	Y ¹	Y
Second Party Advertising Signage	Y	Y ²	N	Y ²
Third Party Signage	Y ²	N	N	N
Y content of sign which is permitted. N Content of sign not permitted. Y ¹ Signage content limited to building name and corporate logos. Y ² Size limited to 2 square metres or 20% of the area of the sign, whichever is the lesser.				

Built Form and Building Design

The following specifications provide possible solutions that should be considered in relation to building design and built form, including height, bulk and scale of buildings and structures associated with a proposed development:

Assessment Outcome	11. The height, bulk and scale of the development is appropriate, noting the desired zone policy outcomes.
Specification	
Building height	10.1. The maximum height of any wall of the buildings is not more than 12 metres above datum ground level.

Sustainability and Environment

The following specifications provide possible solutions that should be considered in relation to the sustainability and environmental outcomes associated with a proposed development:

Assessment Outcome	12. Roofed areas and hard surfaces aim to reduce urban heat island effects and minimise stormwater run-off. This includes consideration of water sensitive urban design measures.
Specification	

Site permeability	12.1. For development on sites greater than 2,000m ² involving works that have the potential to alter the stormwater regime of the site; or development within existing urban areas which increases impervious area by 100m ² , development achieves a minimum of 20% of the site area to be permeable.
Water sensitive urban design	12.2. Development complies with the <i>ACT Practice Guidelines for Water Sensitive Urban Design Module 2: Designing Successful WSUD Solutions in the ACT</i> .

Assessment Outcome	13. Threats to biodiversity such as noise, light pollution, invasive species incursion or establishment, chemical pollution, or site disturbance are avoided or minimised through good design.
No applicable specification for this assessment outcome. Application must respond to the assessment outcome.	

Assessment Outcome	14. Minimise cut and fill to protect natural hydrological function and limit soil erosion and site disturbance.
Specification	
Site disturbance	14.1. For sites less than 3,000m ² , the development complies with the Environment Protection Authority requirements regarding construction and land development. For sites 3,000m ² or greater, the development prepares an erosion and sediment control plan and obtains endorsed by the ACT Environment Protection Authority.

Assessment Outcome	15. The development considers and addresses site constraints, including heritage, natural features, topography, infrastructure and utilities.
No applicable specification for this assessment outcome. Application must respond to the assessment outcome.	

Assessment Outcome	16. Environmental risks, including noise, bushfire, flooding, contamination, air quality or hazardous materials are appropriately considered for the development on the site and surrounding area
Specification	
Noise management – general	<p>14.1. Where any of the following uses are proposed:</p> <ul style="list-style-type: none"> a) Club, b) Drink establishment, c) Emergency services facility, d) General industry, e) Hazardous industry, f) Indoor recreation facility, g) Indoor entertainment facility, h) Offensive industry, i) Outdoor recreation facility, j) Restaurant, <p>development complies with a noise management plan prepared by a suitably qualified person and endorsed by the Environment Protection Authority (EPA).</p>

	<p>Note: The noise management plan will detail the proposed design, siting and construction methods that will be employed to ensure compliance with the Noise Zone Standard as detailed in the <i>Environment Protection Regulation 2005</i>, based on the estimated noise levels when the facility is in use.</p>
Emergency Management Plan – animal care facility	<p>14.2. An Emergency Management Plan is provided for an animal care facility, prepared by a suitably qualified professional, and includes details of a risk assessment and evacuation plan for the facility.</p>
Bushfire prone area	<p>14.3. All development in the bushfire prone area (identified by the Emergency Services Authority) to comply with the ACT Bushfire Management Standards</p>
Flood risk	<p>14.4. Development is to comply with the following:</p> <ul style="list-style-type: none"> a) Residential and commercial buildings are to be excluded from flood liable areas up to the 1% Annual Exceedance Probability (AEP) Flood. b) Habitable floor levels are to be above the 1% AEP level plus a suitable freeboard (usually 300mm). c) In flood liable areas up to the 0.2% Annual Exceedance Probability (AEP) Flood, large developments and those with more sensitive uses* are to be referred to ESA, TCCS and EPSDD for endorsement. <p>Note: *Sensitive uses include developments such as hospitals, nursing homes, childcare centres, prisons, archives, libraries and emergency response centres.</p>
Stormwater retention and detention	<p>14.5. For development on sites greater than 2,000m² (other than major roads) involving works that have the potential to alter the stormwater regime of the site, a report from a suitably qualified person is provided demonstrating that the development complies with:</p> <ul style="list-style-type: none"> a) At least one of the following: <ul style="list-style-type: none"> i) Stormwater retention management measures are provided and achieve all of the following: <ul style="list-style-type: none"> A. Stormwater storage capacity of 1.4kl per 100m² of the total impervious area of the site is provided specifically to retain and reuse stormwater generated on site as a whole. B. Retained stormwater is used on site. ii) Development captures, stores and uses the first 15mm of rainfall falling on the site; and <p>Note: on-site stormwater retention is defined as the storage and use of stormwater on site.</p> <ul style="list-style-type: none"> b) Stormwater detention measures are provided and achieve all of the following: <ul style="list-style-type: none"> i) Capture and direct runoff from the entire site. ii) Stormwater storage capacity of 1kl per 100m² of impervious area is provided to specifically detain stormwater generated on site. iii) The detained stormwater is designed to be released over a period of 6 hours after the storm event. For this rule on-site stormwater detention is defined as the short-term storage and release downstream of stormwater runoff. <p>Note: Calculating on-site detention can include 50% of the volume of rainwater tanks where stormwater is used on-site.</p>
Stormwater management	<p>14.6. For development of roads on sites greater than 2,000m² development meets all of the following:</p> <ul style="list-style-type: none"> a) The capacity of existing pipe (minor) stormwater connection to the site is not exceeded in the 1 in 10-year storm event. b) The capacity of the existing overland (major) stormwater system to the site is not exceeded in the 1 in 100-year storm event.

Stormwater quality	<p>14.7. For development on sites greater than 2,000m² (other than major roads) involving works that have the potential to alter the stormwater regime of the site, a MUSIC model prepared by a suitably qualified person is provided demonstrating the average annual stormwater pollutant export is reduced when compared with an urban catchment of the same area with no water quality management controls for all of the following:</p> <ol style="list-style-type: none"> Gross pollutants by at least 90%. Suspended solids by at least 60%. Total phosphorous by at least 45%. Total nitrogen by at least 40%. <p>Notes:</p> <ul style="list-style-type: none"> If a tool other than the MUSIC model is used then a report by an independent suitably qualified person must be submitted demonstrating and confirming compliance. If parameters that are non-compliant are used then a report must also be submitted by an independent suitably qualified person stating how and why the parameters are appropriate.
Site contamination	14.8. Where development is proposed on a site impacted or potentially impacted by contamination, the development and proposed methods of responding to the contamination is endorsed by the ACT Environment Protection Authority.
Hazardous materials	14.9. Where development is proposed on a site impacted by hazardous materials, the development and proposed methods of managing the hazardous materials is endorsed by the ACT Environment Protection Authority.
Demolition	14.10. Where demolition of commercial or industrial premises for which a certificate of occupancy was issued before 2005 is proposed, demolition is undertaken in accordance with hazardous materials survey (including an asbestos survey) prepared by a suitably qualified person and endorsed by the Environment Protection Authority.

Parking, Services and Utilities

The following specifications provide possible solutions that should be considered in relation to vehicle parking, access and site servicing (including possible requirements by utility providers) for a proposed development:

Assessment Outcome 17. The development provides electric vehicle parking and access to charging locations, where parking is provided.	
Specification	
Electric vehicle ready parking	<p>17.1. This specification applies to:</p> <ol style="list-style-type: none"> New developments. Major alterations and/or extensions to existing buildings (if the work affects more than 50% of the floor area of the whole of an existing building). <p>At least 20% of parking spaces in new industrial developments are EV ready.</p>

Assessment Outcome 18. The development provides appropriate end-of-trip facilities.	
Specification	
End of trip facilities – provision of facilities	<p>18.1. This specification applies to:</p> <ol style="list-style-type: none"> New developments. Major alterations and/or extensions to existing buildings (if the work affects more than 50% of the floor area of the whole of an existing building). Changes of use that require approval of a Development Application. <p>On-site bicycle parking must meet all of the following:</p> <ol style="list-style-type: none"> Spaces for short and long-stay users are to be in accordance with the relevant rates shown in Table 1. Bicycle parking facility must be Security Level A, B or C as set out in AS2890.3. <i>Security levels for long- stay</i> must also be: <ol style="list-style-type: none"> Securely enclosed and separated from publicly accessible areas, including car parking areas. Protected from the weather. Provided on a hard floor surface such as concrete or paving. Be clearly visible, well-lit, secure, safe and well ventilated. Located: <ol style="list-style-type: none"> Long stay - within one level of the building entrance and no more than 30m from this entrance. Short stay - at-grade and on the main access route to the entrance and not more than 30m from a major entrance or destination. Where bicycle parking devices are used: <ol style="list-style-type: none"> Access aisles adjacent to bicycle parking devices must be a minimum width of: <ul style="list-style-type: none"> 1.5m for side-by-side bicycle parking; and 2.0m for multi-tier bicycle parking or bicycle lockers. Access aisles are designed in accordance with <i>as2890.3</i>. Not more than 80% of all bicycle parking spaces are to be multi-tier, in accordance with <i>as2890.3</i>. Bicycle parking devices must accommodate the bicycle space envelope nominated in <i>as2890.3</i>. <p>Net lettable area (nla) is calculated in one of the following ways:</p> <ol style="list-style-type: none"> In accordance with the nla definition. 85% of a building's gross floor area. <p>Note: Wall-mounted bicycle parking devices located above the bonnet of car parking spaces must not be counted toward the provision of bicycle parking required to meet this specification.</p>
End of trip facilities – design requirements of facilities	<p>18.2. This specification applies to:</p> <ol style="list-style-type: none"> New developments. Major alterations and/or extensions to existing buildings (if the work affects more than 50% of the floor area of the whole of an existing building). Changes of use that require approval of a Development Application. <p>The access path to end-of-trip facilities provides a minimum unobstructed width of:</p> <ol style="list-style-type: none"> 1.5m where the number of bicycle movements is less than 30 per hour in peak periods. 2.5m where the number of bicycle movements is 30 or more per hour in peak periods.

	<ul style="list-style-type: none"> c) The access path to end-of-trip facilities must also be in accordance with AS2890.3. d) Ramp gradients must not exceed 1:12 where they are to be ridden by a bicycle rider accessing end-of-trip facilities, in accordance with AS2890.3. e) Bicycle parking facility users must not be required to walk up or down vehicular ramps to access bicycle parking.
End of trip facilities – shower and change facilities	<p>18.3. This specification applies to:</p> <ul style="list-style-type: none"> a) New developments. b) Major alterations and/or extensions to existing buildings (if the work affects more than 50% of the floor area of the whole of an existing building). c) Changes of use that require approval of a Development Application. <p>Shower and change facilities must be provided for long-stay users in non-residential development:</p> <ul style="list-style-type: none"> a) A minimum of one shower is provided for the first 5 long-stay spaces or part thereof, plus an additional shower for each 10 bicycle parking spaces thereafter. b) Shower and change facilities must be rounded up such that an equal number of male and female facilities are provided. c) Separate male and female shower and change facilities must be provided. d) A minimum of one toilet, wash basin and drying area is provided to shower and change facilities. e) A minimum of one change room is provided per shower as one of the following. <ul style="list-style-type: none"> i) A combined shower/change room. ii) Direct access to a communal change room. f) Where a communal change room is provided, direct access is provided via the shower facility, without passing through a publicly accessible area. g) Separate gender-neutral shower and change facilities are provided where possible. h) Personal storage facilities must be provided for long-stay users in non-residential development. i) Personal storage facilities (lockers) must be: <ul style="list-style-type: none"> i) Provided at a rate of 2 for each bicycle parking space provided (lockers may be used by a variety of active travel, recreational and sport user groups). ii) Of suitable volume and dimensions to allow adequate storage of clothing, towels, helmets, footwear and other personal items. iii) Well ventilated, secure and lockable; and iv) Located in one or both of the following locations: <ul style="list-style-type: none"> • Close to shower and change facilities to provide for the safety, privacy and convenience of the user. • Within communal change rooms.

Table 1 – End of trip facilities – provision rates[Link back to specification](#)

Land use	Standard rates for end-of-trip facilities	
	Long-stay users (residents, employees, students)	Short-stay users (customers, patrons, visitors)
Animal care facility	1 space per 4 practitioners or 1 space per 1500m ² NLA	1 space per 2 practitioners or 1 space per 75m ² NLA
Aquatic recreation facility	1 space per 3000m ² NLA	1 space per 150m ² NLA
Bulky goods retailing	1 space per 1750m ² NLA	1 space per 1000m ² NLA
Caravan park/camping ground	1 space per 5 ha	5 spaces per ha
Civic administration	1 space per 200m ² NLA	1 space per 400m ² NLA
Club	1 space per 150m ² NLA	1 space per 150m ² NLA
Community activity centre	1 space per 1500 seats or 1 space per 1500m ² NLA	1 space per 15 seats or 1 space per 15m ² NLA
Community theatre	1 space per 1500 seats or 1 space per 1500m ² NLA	1 space per 15m ² NLA
Cultural facility	1 space per 1200m ² NLA	1 space per 60m ² NLA
Drink establishment	1 space per 150m ² NLA	1 space per 150m ² NLA
Emergency services facility	1 space per 1000m ² NLA	None
Health facility	1 space per 4 practitioners or 1 space per 1500m ² NLA	1 space per 2 practitioners or 1 space per 75m ² NLA
Hospital	1 space per 3 beds or 1 space per 150m ² NLA	1 space per 15 beds or 1 space per 900m ² NLA
Indoor entertainment facility	1 space per 3000m ² NLA	1 space per 150m ² NLA
Indoor recreation facility	1 space per 3000m ² NLA	1 space per 150m ² NLA
Industry	1 space per 800m ² NLA	1 space per 2,000m ² NLA or part thereof
Light industry	1 space per 800m ² NLA	1 space per 2,000m ² NLA or part thereof
Municipal depot	1 space per 2 ha	None
Business agency, financial establishment, office, public agency	1 space per 200m ² NLA	1 space per 400m ² NLA
Personal service	1 space per 500m ² NLA	2 spaces, plus 1 space per 1000m ² NLA above 2000m ² NLA
Place of assembly	1 space per 1500 seats or 1 space per 1500m ² NLA	1 space per 15 seats or 1 space per 15m ² NLA

Place of worship	1 space per 1500 seats or 1 space per 1500m ² NLA	1 space per 15 seats or 1 space per 15m ² NLA
------------------	---	---

Land use	Standard rates for end-of-trip facilities	
	Long-stay users (residents, employees, students)	Short-stay users (customers, patrons, visitors)
Religious associated use	1 space per 1500 seats or 1 space per 1500m ² NLA	1 space per 15 seats or 1 space per 15m ² NLA
Restaurant	1 space per 150m ² NLA	1 space per 150m ² NLA
Scientific research establishment	1 space per 150m ² NLA	None
Retail plant nursery, supermarket,	1 space per 250m ² NLA	1 space per 100m ² NLA
Supermarket	1 space per 600m ² NLA	1 space per 200m ² NLA
Take-away food shop	1 space per 250m ² NLA	1 space per 100m ² NLA
Veterinary hospital	1 space per 300m ² NLA	1 space per 300m ² NLA
Warehouse	1 space per 800m ² NLA	1 space per 2,000m ² NLA or part thereof

Individual assessments are required for any other development type not listed above.

Assessment Outcome	19. Vehicle and bicycle parking sufficiently caters for the development while minimising visual impacts from the street or public space. This includes consideration of parking location, dimensions and number of spaces provided.
Specification	
Number of car parking spaces	19.1. Parking spaces are provided on site at the rate Table 2 and location in Table 3 .
Accessible car parking spaces	19.2. Accessible parking meets the following: <ul style="list-style-type: none"> a) Parking spaces for people with disabilities in public car parks of more than 10 spaces comprise a minimum of 3% (rounded up to the nearest whole number) of the total number of parking spaces required for the development. b) Car parking spaces provided for people with disabilities have vertical clearance for the entire width of the space and the adjacent shared area of not less than 2.5m - as described in AS2890.
Dimensions and access for car parking spaces	19.3. Dimensions of car parking spaces, layout and vehicle manoeuvring meet: <ul style="list-style-type: none"> a) AS 2890.1:2004, <i>the Australian Standard for Parking Facilities, Part 1: Off-street Car Parking including manoeuvring to and from and within the development, sightlines and gradients</i>. b) Australian Standard AS/NZS 2890.6:2009 <i>Parking Facilities – Part 6: Off-street parking for people with disabilities</i>.

Safety	19.4. Verge crossings and internal driveways are designed to be safely used by both pedestrians, cyclists and vehicles, such as through the use of vehicle speed reduction measures.
Pedestrian and cyclist access	19.5. Pedestrian and cyclist entrances, and driveways to the site are clearly visible from the front boundary, provided through the site to increase permeability, feed into and provides connections to existing path networks and on-road cycle routes. Priority is provided for pedestrian and cyclist access
Accessible path of travel	<p>19.6. Development complies with the following:</p> <ul style="list-style-type: none"> a) A continuous accessible path of travel is provided that complies with: <ul style="list-style-type: none"> i) <i>AS 1428.1 – Design for Access and Mobility.</i> ii) <i>AS 1428.4 – Tactile ground surface indicators for the orientation of people with vision impairment to highlight hazards or provide direction.</i> iii) <i>AS 4586 – Slip Resistant Classification of New Pedestrian Surface Materials for external paving and ground surfaces.</i> iv) designed so that the placement of facilities does not intrude into the continuous accessible path of travel. b) Walkways and glass adjacent to walkways achieve compliance with <i>AS1428.1</i> and <i>AS1428.2</i>. c) Internal lighting along the whole of the continuous accessible path of travel designed to meet <i>AS1680.0</i>. d) External lighting along the whole of the continuous accessible path of travel meets <i>AS1158.3.1</i>. e) Directional signage or other wayfinding methods, e.g., tactile indicators, to be in accordance with <i>AS1428.1</i> and <i>AS1428.4</i> and must identify the continuous accessible path of travel, accessible parts of buildings and all accessible facilities. f) Doorways and doors are designed to meet <i>AS 1428.1- Design for Access and Mobility for pedestrian entrances and exits; public circulation areas; and any common use areas.</i>

Table 2 and 3 – Parking rates and location requirements

[Link back to specification](#)

Table 2 - Parking provision rates for IZ zones

Development	I21	I22
Animal care facility	1 space / facility; plus 2 spaces per 15 animals for employee parking; plus visitor parking as follows: 2 spaces: <30 animals per facility 3 spaces: 30-59 animals per facility 4 spaces: 60-90 animals per facility plus 1 pick-up/set-down bay per 10 animals	
Business agency	N/A	6 spaces / 100m ² GFA
Bulky goods retailing	N/A	3 spaces / 100m ² 2 GFA
Community activity centre	4 spaces / 100m ² GFA	
Community theatre	1 space / 4 seats	
Craft workshop	4 spaces / 100m ² GFA	

Development	IZ1	IZ2
Cultural facility	2 spaces / 100m ² GFA	
Drink establishment	N/A	15 spaces / 100m ² GFA
Emergency services facility	1 space/peak shift employee	
Financial establishment	N/A	6 spaces / 100m ² GFA
Funeral parlour	N/A	2 spaces / 100m ² GFA excluding chapel area; plus 1 space / 4 chapel seats
General industry	2 spaces / 100m ² GFA	
Hazardous industry	1 space / peak shift employee	N/A
Hazardous waste facility		
Health facility	4 spaces / practitioner	
Hospital	0.8 spaces / peak shift employee plus 1.3 spaces / bed	
Incineration facility	1 space / peak shift employee	N/A
Indoor entertainment facility	N/A	To meet requirements of CZ3 zone
Indoor recreation facility	<i>See below</i>	
Basketball, netball	20 spaces/court	
Skating rink/swimming pool	10 spaces/100m2 of actual pool or rink area	
Squash courts	2 spaces/court	
Fitness Centre/ gymnasium	2 spaces/100m ² GFA	
Industrial Trades	2 spaces / 100m ² GFA	
Light industry		
liquid fuel depot	1 space / peak shift employee	
municipal depot		
offensive industry	1 space / peak shift employee	N/A
Office	N/A	2 spaces / 100m ² GFA
Outdoor recreation facility	N/A	To meet requirements of CZ3 zone
Personal service	N/A	4 spaces / 100m ² GFA
Place of worship	1 space / 4 seats	
Public agency	N/A	4 spaces / 100m ² GFA
Recycling facility	1 space / peak shift employee	
Restaurant	N/A	15 spaces / 100m ² GFA
Scientific research establishment	2 spaces / 100m ² of office and laboratory space; plus individual assessment of provision for other activities	
Service station	6 spaces/service bay plus 4 spaces/100m2 of shop area	
Supermarket	N/A	5 spaces / 100m ² GFA

Development	IZ1	IZ2
Takeaway food shop		
Storage facility	2 spaces / 100m ² GFA	
Vehicle sales	N/A	6 spaces / service bay plus 6 spaces / 100m ² of sales area
Veterinary clinic	N/A	3 spaces / 100m ² GFA
Veterinary hospital	N/A	3 spaces / 100m ² GFA
Warehouse	1 space / 100m ² GFA plus 2 spaces / 100m ² GFA of office space	
Waste transfer station	1 space / peak shift employee	

Table 3 - Parking locational requirements

[Link back to specification](#)

Location or use ¹	Long stay parking	Short stay / Visitor	Operational parking ²
Industrial Zones			
Personal service (commercial sexual service)	On-site (concealed from the road for employee safety)	On-site or within 100m	On-site
All other development in industrial zone	On-site or within 200m	On-site or within 100m	On-site

Note

¹ Distances are actual **walking** distance, not radius or direct line distance.

² Operational parking is for vehicles used directly as part of the operation within the development.

Assessment Outcome	20. Waste is appropriately managed on site without having a detrimental impact on users and the surrounding area.
Specification	
Waste facilities	20.1. Developments that propose post occupancy waste management facilities achieve endorsement from Transport Canberra and City Services (TCCS).

Assessment Outcome	21. The site is appropriately serviced in terms of infrastructure and utility services and any associated amenity impacts are minimised.
Specification	

Servicing and infrastructure	21.1. Proposed development can be sufficiently serviced in terms of infrastructure and utility services. Endorsement is achieved from relevant utility providers (electricity, water, gas, sewerage and stormwater) to confirm that the location and nature of earthworks, utility connections, proposed buildings, pavements and landscape features comply with utility standards, access provisions and asset clearance zones.
Battery storage	21.1 Where development includes a battery over 30kW, the development is endorsed by the Emergency Services Agency.
Demolition – utility endorsement	21.2 For demolition works, endorsement is achieved from relevant utility providers (electricity, water, gas, sewerage and stormwater) stating that: <ul style="list-style-type: none"> a) All network infrastructure on or immediately adjacent the site has been identified on the plan. b) All potentially hazardous substances and conditions (associated with or resulting from the demolition process) that may constitute a risk to utility services have been identified. c) All required network disconnections have been identified and the disconnection works comply with utility requirements. d) All works associated with the demolition comply with and are in accordance with utility asset access and protection requirements.
Loading docks and goods vehicles	21.3 Development complies with the following: <ul style="list-style-type: none"> a) Goods loading and unloading facilities are located within the site and allow for service vehicles to enter and leave the site in a forward direction. b) Loading docks or vehicular entries to buildings are not located on frontages to the street. c) Endorsement by Transport Canberra and City Services (TCCS) to confirm goods loading and unloading facilities are appropriate. <p>Note: Loading, unloading and associated manoeuvring areas are in addition to minimum parking requirements.</p>
External lighting	21.4 Development complies with the following: <ul style="list-style-type: none"> a) External lighting is provided to building frontages, to all pathways, roads, laneways and car-parking areas in accordance with <i>Australian Standard AS1158.3.1 Pedestrian Lighting</i>. b) All external lighting provided is in accordance with <i>Australian Standard AS4282 - Control of the Obtrusive Effects of Outdoor Lighting</i>.
Encroachment of easements and rights-of-way	21.5 Buildings do not encroach over easements or rights of way, unless the proposed encroachment is approved in writing by the relevant service provider.